

ICS 33.070.99
CCS M 37

YD

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

YD/T 1721.2-2011

Replacing YD/T 1721.2-2007

**2GHz TD-SCDMA digital cellular mobile telecommunication network.
HSDPA physical layer technical requirement. Part 2: Physical channels
and mapping of transport channels onto physical channels**

2GHz TD-SCDMA数字蜂窝移动通信网 高速下行分组接入（HSDPA）Uu接口物理
层技术要求 第2部分：物理信道和传输信道到物理信道的映射

(English Translation)

Issued on: June 1, 2011

Implemented on: June 1, 2011

Issued by: Ministry of Industry and Information Technology

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the 2GHz TD-SCDMA digital cellular mobile communication network speed downlink packet access (HSDPA) Uu interface physical layer provides a high level of service, the physical characteristics of the channel and the transmission channel to the physical channel mapping process. This standard applies to 2GHz TD-SCDMA digital cellular mobile communication network speed downlink packet access (HSDPA) Uu interface physical layer.

Document data

International classification (ICS): 33.070.99.

Chinese classification (CCS): M37.

Estimated length of the Chinese original: 47,436 words.

Adopted international standard: 3GPP TS25.221 v5.7.0, MOD.

Supersedes the earlier edition YD/T 1721.2-2007.

Standards quoted by this document

YD/T 1721.4