

ICS 33.070.99
CCS M 37

YD

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

YD/T 1721.6-2011

Replacing YD/T 1721.6-2007

**2GHz TD-SCDMA digital cellular mobile telecommunication
network. HSDPA physical layer technical requirement. Part 6:
Physical layer measurement**

2GHz TD-SCDMA数字蜂窝移动通信网 高速下行分组接入 (HSDPA) Uu接口物理
层技术要求 第6部分: 物理层测量

(English Translation)

Issued on: June 1, 2011

Implemented on: June 1, 2011

Issued by: Ministry of Industry and Information Technology

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the 2GHz TD-SCDMA digital cellular mobile communication network speed downlink packet access (HSDPA) Uu Interface UE and network measurement descriptions and definitions, including the UE/UTRAN measurement control, UTRA TDD measurement capability. This standard applies to 2GHz TD-SCDMA digital cellular mobile communication network speed downlink packet access (HSDPA) Uu interface physical layer.

Document data

International classification (ICS): 33.070.99.

Chinese classification (CCS): M37.

Estimated length of the Chinese original: 18,112 words.

Adopted international standard: 3GPP TS25.225, NEQ.

Supersedes the earlier edition YD/T 1721.6-2007.

Standards quoted by this document

YD/T 1721.2; YD/T 1721.5; YD/T 1723; 3GPP TS25.102; 3GPP TS25.123; 3GPP TS25.105