

ICS 33.070.99
CCS M 37

YD

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

YD/T 1724.4-2011

Replacing YD/T 1724.4-2007

**2GHz TD-SCDMA digital cellular mobile telecommunication
network. HSDPA Iub interface technical requirement. Part 4:
NBAP signalling**

2GHz TD-SCDMA数字蜂窝移动通信网 高速下行分组接入（HSDPA）Iub接口技
术要求 第4部分：NBAP信令

(English Translation)

Issued on: May 18, 2011

Implemented on: June 1, 2011

Issued by: Ministry of Industry and Information Technology

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the 2GHz TD-SCDMA digital cellular mobile communication network lub interface, a wireless network layer signaling protocol: Node B Application Part (NBAP). This standard specifies the lub interface, NBAP support functions implemented through the signaling process. This standard applies to 2GHz TD-SCDMA digital cellular mobile communication network speed downlink packet access (HSDPA) the lub interface.

Document data

International classification (ICS): 33.070.99.

Chinese classification (CCS): M37.

Estimated length of the Chinese original: 645,692 words.

Adopted international standard: 3GPP TS 25.433 V5.d.0, NEQ.

Supersedes the earlier edition YD/T 1724.4-2007.

Standards quoted by this document

YD/T 1721.2; YD/T 1721.4; YD/T 1721.5; YD/T 1721.6; YD/T 1722.1; YD/T 1723; YD/T 1724.1; YD/T 1724.6; YD/T 1724.7; YD/T 1724.8; 3GPP TS 25.105; 3GPP TS 25.123; 3GPP TS 25.212; 3GPP TS 25.213; 3GPP TS 25.302; 3GPP TS 25.402; 3GPP TS 25.433; 3GPP TS 25.434; 3GPP TS 25.921; 3GPP TS 25.133