

ICS 33.060
CCS M 36

YD

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

YD/T 1847.2-2009

**Technical Requirement for Uu interface of 2GHz TD-SCDMA.
Digital Cellular Mobile Communication network HSUPA. Part 2:
Layer 1**

2GHz TD-SCDMA 数字蜂窝移动通信网 高速上行分组接入(HSUPA)Uu接口物理层
技术要求 第2部分: 层1

(English Translation)

Issued on: June 15, 2009

Implemented on: September 1, 2009

Issued by: Ministry of Industry and Information Technology

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the 2GHz TD-SCDMA digital cellular mobile communication network High Speed Uplink Packet Access (HSUPA) Iub interface layer used a standard. This standard applies to 2GHz TD-SCDMA digital cellular mobile communication network High Speed Uplink Packet Access (HSUPA) Iub interface. Transmission delay requirements and O & M requirements are not within the scope of this section.

Document data

International classification (ICS): 33.060.

Chinese classification (CCS): M36.

Estimated length of the Chinese original: 8,894 words.

Adopted international standard: 3GPP TS 25.431 v7.0.0, NEQ.

Standards quoted by this document

3GPP TS 25.411; ITU-T I.432.1-8-1996; ITU-T I.432.2-8-1996; ITU-T G703-10-1998; ITU-T G704-10-1998; ITU-T G957-7-1995; ITU-T G823-3-1993; ITU-T G824-3-1993; ITU-T G825-3-1993; ITU-T G826-8-1996; ATM Forum AF-PHY-0086.001-2-1999; ATM Forum AF-PHY-0064.000-11-1996; ATM Forum AF-ARCH-0913.000-11-2002; IEEE 802.3