

ICS 33.060
CCS M 36

YD

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

YD/T 1847.3-2009

**Technical Requirement for Uu interface of 2GHz TD-SCDMA.
Digital Cellular Mobile Communication network HSUPA. Part 3:
Signalling transport**

2GHz TD-SCDMA 数字蜂窝移动通信网 高速上行分组接入(HSUPA)Uu接口物理层
技术要求 第3部分: 信令传输

(English Translation)

Issued on: June 15, 2009

Implemented on: September 1, 2009

Issued by: Ministry of Industry and Information Technology

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the 2GHz TD-SCDMA digital cellular mobile communication network High Speed ??Uplink Packet Access (HSUPA) Iub interface using the signaling transmission technology requirements. This standard applies to 2GHz TD-SCDMA digital cellular mobile communication network High Speed ??Uplink Packet Access (HSUPA) Iub interface. Transmission delay requirements and operation and maintenance requirements are not part of the scope of this section.

Document data

International classification (ICS): 33.060.

Chinese classification (CCS): M36.

Estimated length of the Chinese original: 13,136 words.

Adopted international standard: 3GPP TS 25.432 V7.1.0, NEQ.

Standards quoted by this document

ITU-T Q.2100; ITU-T Q.2130; ITU-T Q.2110; ITU-T I.363.5; ITU-T I.361; IETF RFC 2960; IETF RFC 2460; IETF RFC 791; IETF RFC 2474; IETF RFC 1661; IETF RFC 1662; IETF RFC 2507; IETF RFC 1990; IETF RFC 2686; IETF RFC 2509; IETF RFC 3153; IETF RFC 3031; IETF RFC 3309; IEEE 802.3; IEEE 802.1P; IEEE 802.1Q; IEEE 802.3 X