

**INDUSTRY STANDARD OF THE  
PEOPLE'S REPUBLIC OF CHINA**

**YD/T 1847.5-2009**

---

**Technical Requirement for Uu interface of 2GHz TD-SCDMA  
Digital Cellular Mobile Communication network HSUPA. Part 5:  
Data transport and transport signalling for CCH data streams**

2GHz TD-SCDMA 数字蜂窝移动通信网 高速上行分组接入(HSUPA)Uu接口物理层  
技术要求 第5部分：公共传输信道数据流的数据传输和传输信令

**(English Translation)**

**Issued on: June 15, 2009**

**Implemented on: September 1, 2009**

---

**Issued by: Ministry of Industry and Information Technology**

## Table of Contents

|                                         |   |
|-----------------------------------------|---|
| What this standard covers .....         | 1 |
| Document data .....                     | 2 |
| Standards quoted by this document ..... | 3 |

### What this standard covers

This standard specifies the 2GHz TD-SCDMA digital cellular mobile communication network High Speed Uplink Packet Access (HSUPA) Iub interface used for public transport channel data stream data transfer and transport signaling. This standard applies to 2GHz TD-SCDMA digital cellular mobile communication network High Speed Uplink Packet Access (HSUPA) Iub interface.

### Document data

International classification (ICS): 33.060.

Chinese classification (CCS): M36.

Estimated length of the Chinese original: 11,181 words.

Adopted international standard: 3GPP TS 25.434 V7.2.0, NEQ.

### Standards quoted by this document

YD/T 1847.7; ITU-T E.164; ITU-T I.361; ITU-T I.363.2; ITU-T I.366.1; ITU-T Q.2630.1; ITU-T Q.2150.2; ITU-T Q.2630.2; IEEE 802.1P; IEEE 802.1Q; IEEE 802.3; IEEE 802.3X; IETF RFC 2460; IETF RFC 791; IETF RFC 1661; IETF RFC 1662; IETF RFC 1990; IETF RFC 2474; IETF RFC 2475; IETF RFC 2507; IETF RFC 2509; IETF RFC 2364; IETF RFC 2686; IETF RFC 3031; IETF RFC 3153; IETF RFC 3376; IETF RFC 3810