

ICS 33.060.99
CCS M 36

YD

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

YD/T 1974-2009

**Test methods for 800MHz/2GHz cdma2000 digital cellular
mobile telecommunication network broadcast-multicast service
equipment. Access terminal**

800MHz/2GHz cdma2000数字蜂窝移动通信网 广播多播业务(BCMCS)设备测试
方法 接入终端(AT)

(English Translation)

Issued on: December 11, 2009

Implemented on: January 1, 2010

Issued by: Ministry of Industry and Information Technology

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the 800MHz/2GHz cdma2000 digital cellular mobile communication network Broadcast Multicast Service (BCMCS) device access terminal functions, RF indicators, environmental adaptability, testing methods. This standard applies to support UIM card (UIM) and does not support the UIM card (machine card) of 800MHz/2GHz cdma2000 digital cellular mobile communication network Broadcast Multicast Service (BCMCS) device access terminals. For the support of the UIM card 800MHz/2GHz cdma2000 digital cellular mobile communication network Broadcast Multicast Service (BCMCS) device access terminal, this standard applies to all projects. Do not support the UIM card 800MHz/2GHz cdma2000 digital cellular mobile communication network Broadcast Multicast Service (BCMCS) device access terminal, this standard involves the UIM card and UIM card interface test items do not apply.

Document data

International classification (ICS): 33.060.99.

Chinese classification (CCS): M36.

Estimated length of the Chinese original: 20,262 words.

Standards quoted by this document

GB/T 18287; GB/T 18288; GB/T 18289; YD 1268.1; YD 1268.2; YD/T 965; YD/T 1539; YD/T 1567-2009; YD/T 1670-2009; YD/T 1680 - 2009; YD/T 1681-2009; IETF RFC 3095; YD/T 1644.1