

ICS 33.060.20
CCS M 37

YD

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

YD/T 2205-2011

**Test method for 800MHz/2GHz CDMA2000 digital cellular mobile
telecommunication network. High rate packet data (Phase 3)
equipment. Access terminal**

800MHz 2GHz cdma2000数字蜂窝移动通信网 高速分组数据（HRPD）（第三阶段）设备测试方法 接入终端（AT）

(English Translation)

Issued on: June 1, 2011

Implemented on: June 1, 2011

Issued by: Ministry of Industry and Information Technology

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the 800MHz/2GHz CDMA2000 digital cellular mobile communication network High Rate Packet Data (HRPD) function (the third stage) access terminal, layers of performance, environmental adaptability, life, power supply and battery charger, appearance of the packaging and assembly the test methods. This standard applies to support UIM card (UIM) and does not support the UIM card (machine card) of 800MHz/2GHz CDMA2000 HRPD (third stage) access terminals. For support UIM card 800MHz/2GHz CDMA2000 HRPD (third stage) access terminal, this standard are applicable to all projects, UIM cards that do not support 800MHz/2GHz CDMA2000 HRPD (third stage) access terminal, this standard involves UIM card interface test items do not apply.

Document data

International classification (ICS): 33.060.20.

Chinese classification (CCS): M37.

Estimated length of the Chinese original: 114,154 words.

Adopted international standard: 3GPP2 C.S0033-B V1.0, NEQ.

Standards quoted by this document

GB 2312-1980; GB 4943; GB 13000.1-1993; GB/T 18287; GB/T 18288; GB/T 18289; YD 1268.1; YD/T 1539; YD/T 1591; YD/T 1597.1; YD/T 1644.1; YD/T 1683; YD/T 2206-2011; YDC 023-2006; 3GPP2 C.S0011; 3GPP2 C.S0024-B; 3GPP2 C.S0029-B; 3GPP2 C.S0033-B; 3GPP2 C.S0057-0; ANSI C63.4-2000; CRF TITLE47-1998