

ICS 33.060.20
CCS M 36

YD

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

YD/T 2227-2011

**Test methods for 2GHz TD-SCDMA digital cellular mobile
telecommunication network analog repeater network
management interface**

2GHz TD-SCDMA 数字蜂窝移动通信网模拟直放站设备网管接口测试方法
(English Translation)

Issued on: June 1, 2011

Implemented on: June 1, 2011

Issued by: Ministry of Industry and Information Technology

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the 2GHz TD-SCDMA digital cellular mobile communication network covering the analog repeater and repeater equipment (hereinafter collectively referred to as "repeater") network interface performance and functional testing method in which network interface performance tests include communication, real-time, communication protection timer, fault tolerance and safety performance test, including configuration management interface functional testing, performance data acquisition, fault alarm and remote upgrade feature tests. This standard applies to 2GHz TD-SCDMA digital cellular mobile communication network simulation repeater equipment network management interface, not included in the mobile communication network base station subsystem indoor distribution system network management center, Tamerlan, base station amplifier can refer to other similar products used.

Document data

International classification (ICS): 33.060.20.

Chinese classification (CCS): M36.

Estimated length of the Chinese original: 48,498 words.

Standards quoted by this document

YD/T 2226-2011