

ICS 33.120.10
CCS M 42

YD

**INDUSTRY STANDARD OF THE
PEOPLE'S REPUBLIC OF CHINA**

YD/T 2338-2011

**Telecommunication cable-foamed polyethylene dielectric, copper-clad aluminum
tube inner conductor, corrugated copper tube outer conductor, 50 ohm radio
frequency coaxial cable, for wireless communications**

通信电缆 无线通信用50Ω泡沫聚乙烯绝缘、铜包铝管内导体、皱纹铜管外导体射
频同轴电缆

(English Translation)

Issued on: December 20, 2011

Implemented on: December 20, 2011

Issued by: Ministry of Industry and Information Technology

Table of Contents

What this standard covers	1
Document data	2
Standards quoted by this document	3

What this standard covers

This standard specifies the wireless communication with 50° foam polyethylene insulation, copper clad aluminum conductors inside, corrugated copper tube outer conductor RF coaxial cable (hereinafter referred to as cable) requirements, test methods, inspection rules, signs, packaging, transport and storage. This standard applies to wireless communication devices connected between the antenna and radio frequency electronic equipment, the operating frequency range of 150MHz ~ 2500MHz wireless communication polyethylene foam insulation with 50°, copper clad aluminum conductors inside, corrugated copper tube outer conductor RF coaxial cable.

Document data

International classification (ICS): 33.120.10.

Chinese classification (CCS): M42.

Estimated length of the Chinese original: 18,120 words.

Standards quoted by this document

GB/T 228; GB/T 2951.11-2008; GB/T 2951.13-2008; GB/T 4437.1-2000; GB/T 4909.5; GB/T 6995.3-2008; GB/T 8806; GB/T 11091-2005; GB/T 15065; GB/T 17737.1-2000; GB/T 18380.12-2008; GB/T 18380.35-2008; YD/T 322-1996; YD/T 837.3-1996; YD/T 837.4-1996; YD/T 837.5-1996; YD/T 886-1997; YD/T 897.1-1997; JB/T 8137; JB/T 10696.8-2007; JB/T 10707-2007